



PRODUCT INFORMATION BULLETIN

CARE AND UPKEEP OF GEL COAT SURFACED FIBERGLASS REINFORCED PANELS USED IN HORSE TRAILERS

Maintaining the exterior surface of Gel Coat finished panel used on your horse trailers is easy, with a little care and attention to detail. Following the simple periodic maintenance tips and practices listed below you can minimize many of the detrimental effects of the environment and general wear and tear.

Your unit's roof construction is a tough, resilient structural composite core product, surfaced with polyester gel coat paint. Gel Coat is designed for outstanding weather ability and durability.

- Tip #1** Regularly inspect the unit's roof for signs of damage, nicks and scratches or stains.
- Tip #2** Although gel coat is extremely stain resistant, the staining agent should be removed as soon as possible, as prolonged exposure to sunlight can modify some stains, making them more difficult to remove.
- Tip #3** Washing stains with a mild detergent and water is usually sufficient to remove most stains and deposits.
- Tip #4** Wash and wax at least twice yearly to restore gloss and protect the finish. Use only wax recommended for fiberglass and follow instructions carefully. Never wax a gel coat surface in direct sunlight.
- Tip #5** Minor scratches and nicks can be easily repaired and painted over following simple procedures outlined in Fiber-Tech repair manuals and videos. Contact Fiber-Tech Customer Service Dept. at 800-879-4377.

The suggestions and information presented herein, we believe to be reliable. They are offered in good faith but without guarantee since conditions and methods of use of Fiber-Tech products are beyond Fiber-Tech's control. It is recommended that the prospective user determine the suitability of our material, information and suggestions before adapting them on a commercial scale.

file: Product Info Bulletin – Care & Upkeep of FRP Horse Trailers.doc